










**AVI101N Bio**

-  Face
-  Advance Fingerprint Sensor
-  RFID Card
-  Access Control
-  TCP/IP
-  USB Host & Client
-  Battery Backup

## Multi-Bio Time Attendance and Access Control System

- Face Capacity : 300
  - Fingerprint Capacity : 3000
  - Max. user : 300
  - Log Capacity : 1,60,000
  - Password capacity : 300
  - Card capacity : 300
  - Communication : TCP/IP, USB (host and slave)
  - Push data : Yes (Optional)
  - FRR : 0.001%
  - FAR : 0.00001%
  - CPU : Industrial High Speed CPU
  - RF card options : 125kHz EM (Standard) / 13.56MHz Mifare (Optional)
  - Sensor type : 500 DPI
  - LCD display : 2.8" TFT color screen 320x240 pixel
  - Voice instruction : 16-bit Hi-Fi voice & sound indication
  - Wiegand in & out : Yes
  - Relay : Yes
  - Language : English
  - Verification time : <=1 second
  - Power source : 5VDC/2A
  - Built-in backup battery : Yes
  - Operating temperature : 0°c - 45°c
  - Dimensions (mm) : 190 x 145 x 32
  - Weight (kg) : 0.7
  - Software : Yes
- Features :-**
- World-class algorithm
  - High-Speed and Accurate Fingerprint Identification
  - Face, Fingerprint, Pin, Card authentication
  - 2 output relay for door open.
  - Self-Service Inquiry