



AVI 200 N



Face



Advance Fingerprint Sensor



RFID Card



Access Control



TCP/IP



USB Host & Client



Battery Backup

Multi-Bio Time Attendance with Access Control Functions

- Face Capacity : 3000
 - Fingerprint Capacity : 10,000
 - Max. user : 3000
 - Log Capacity : 2,00,000
 - Password capacity : 3000
 - Card capacity : 3000
 - Communication : TCP/IP, USB (host and slave)
 - Push data : Yes
 - FRR : 0.001%
 - FAR : 0.00001%
 - CPU : 1 GHz
 - RF card options : 125kHz EM (Standard) / 13.56MHz Mifare (Optional)
 - Sensor type : 500 DPI
 - LCD display : 2.8" TFT color screen 320x240 pixel
 - Voice instruction : 16-bit Hi-Fi voice & sound indication
 - Wiegand in & out : Yes
 - Relay : Yes
 - Language : English
 - Operating System : Linux
 - Verification time : ≤ 1 second
 - Power source : 12VDC/2A
 - Built-in backup battery : Yes
 - Operating temperature : -10° - 45°
 - Dimensions (mm) : 190 x 145 x 32
 - Weight (kg) : 0.7
 - Software : Yes
- Features :-**
- World-class algorithm
 - High-Speed and Accurate Fingerprint Identification
 - Face, Fingerprint, Pin, Card authentication
 - 2 output relay for door open.
 - Self-Service Inquiry